

Joint cutter

CF•13.3 B



The flexible joint cutter is particularly suitable for light road restoration as well as gardening and landscaping. Due to its compact dimensions and easy handling the machine is ideal suitable for the rental business.

- Optimized blade protection for maximum saw blade Ø 500 mm
- Reliable Honda gasoline engine with cyclone air filter
- Quick, easy change of cutting side
- Infinitely variable cutting depth adjustment by means of hand crank
- Adjustable cutting depth display and parking brake
- Height-adjustable and low-vibration push bar
- Water supply via 23-litre water tank or external pressurised water connection possible
- Removable transport handle, crane eyelet



CEDIMA® Joint cutter CF-13.3 B



Technical data and equipment features

Drive motor*	
Manufacturer	Honda
Type	GX 390 UT2-SN-C-OH
Mode	air-cooled, 1-cylinder, 4-stroke, petrol
	complies with the strictest emission regulations in the world
Output*	8.7 kW (11,7 PS) / 3 600 min ⁻¹
Cubic capacity*	389 cm ³
Engine ignition device	pull-wire starter
Fuel consumption at continuous output	3.5 l/h
Fuel tank capacity	6.1 l
Feed	Manually via adjustable, vibration-damped push handle
Diamond saw blade receptacle	right or left (in feed direction)
Saw blade receiving pin Ø	25.4 mm (with central hexagon clamping nut SW 24, right: left-hand thread, left: right-hand thread)
Max. saw blade clamping range	13 mm
Driving pin Ø	8 mm
Cutting shaft speed	2 400 min ⁻¹
Diamond saw-blade Ø	300 mm – 500 mm
Max. cutting depth	up to 195 mm
Lifting/lowering of the cutting shaft	Manual via lockable hand crank (threaded spindle)
Dimensions and weight	
length x width x height	approx. 890 mm x 610 mm x 114 mm (transport)
Total weight	approx. 104 kg
Water tank, water filling quantity	removable, approx. 23 l

* motor operating manual is decisive

