

MOVING YOU FURTHER

HX145LCR

With Tier 4 final / Stage IV Engine installed



*Photo may include optional equipment.

Net Power

SAE J1349 / 87 kW (116 HP) at 1,950 rpm

Gross Power

SAE J1995 / 92.7 kW (124 HP) at 1,950 rpm

Travel Speed

5.5 km/hr (3.4 mph) / 3.3 km/hr (2.1 mph)

Operating Weight

15,160 kg / 33,420 lb



RULE THE GROUND

The HX Series excavators are products of HHI's spirit of initiative, creativity and strong drive. HHI's engineers, who are the best in the industry, have worked tirelessly to offer a zero-defect product. The new HX Series reflects customers' needs in the field gleaned by thorough monitoring. They maximize fuel efficiency and performance proven by rigorous field tests and quality control.



*Photo may include optional equipment.

RULE THE GROUND

HX145LCR

The HX series exceeds customers' expectation!
Become a true leader on the ground with HHI's HX series.



WORK MAX, WORTH MAX

- ECO Gauge
- IPC (Intelligent Power Control)
- New Variable Power Control
- Electronic Viscous Fan Clutch
- Attachment Flow Control (Option)
- New Cooling System with Increased Air Flow
- Enlarged Air Inlet with Grill Cover
- Cycle Time Improvement



MODERN COMFORT, SIMPLE AND SAFE SOLUTION

- Easy Access to DEF/AdBlue® Supply System
- Hi MATE (Remote Management System) (Option)
- Viscous Suspension Mount
- Swing Lock System (Option)
- Fine Swing Control (Option)



MORE RELIABLE, MORE SUSTAINABLE

- Durable Cooling Module
- Reinforced Pin, Bush and Polymer Shim
- Reinforced Durability of Upper and Lower Structure and Attachments
- Hi-grade (High-pressure) Hoses



INFOTAINMENT FRONTIER

- Intelligent and Wide Cluster
- Wi-Fi Direct with Smart Phone (Miracast)
- Proportional Auxiliary Hydraulic System
- New Audio System
- New Air Conditioning System

*Photo may include optional equipment.



Cycle Time Improvement

The HX Series provides higher productivity on the site by faster operation.

*Photo may include optional equipment

WORK MAX, WORTH MAX

Fuel Efficient System, Allows Great Performance

The HX Series has an eco-friendly, high-performance engine which ensures both excellent fuel efficiency and high power. With outstanding operating performance proven by rigorous tests at various work sites, it will satisfy any customer's needs.



ECO Gauge

ECO Gauge enable economic operation of machines. The gauge level and color displays engine torque and fuel efficiency level. On top of that, the status of fuel consumption such as average rate and the total amount of fuel consumed are displayed. Hourly and daily based fuel consumption can be checked in the detailed menu as well.



IPC (Intelligent Power Control)

The IPC controls power control depending on work environments. Its mode can be selected and released on the monitor. On the excavation mode, pump flow can be easily controlled by a lever, reducing fuel consumption.



Attachment Flow Control

The HX Series improves pump flow rate by independent control of two pumps. It optimizes attachments for effective flow rate setting depending on attachments (ten breaker types and ten crusher types), enabling various operations matching the site environments.

New Variable Power Control

The HX Series minimizes equipment input and output control signals to improve fuel efficiency. Its three-stage Power mode ensures the highest performance in any operating environment.

* P (power) mode: Maximizes speed and power of the equipment for heavy load work.

* S (standard) mode: Optimizes performance and fuel efficiency of the equipment for general load work.

* E (economy) mode: Improves the control system for light load work.

Electronic Viscous Fan Clutch

The electronic fan clutch reduces noise during operation by precisely controlling RPM depending on the hydraulic oil and coolant temperature of the working vehicle, and minimizes fuel consumption. It is also possible to shorten the warm up time of hydraulic oil.

Enlarged Air Inlet with Grill Cover

Enlarged vent hole of the air inlet side cover and fine net grill to prevent penetration of foreign materials further improve durability.

MORE RELIABLE, MORE SUSTAINABLE

New Exterior Design for Robustness and Safety

The true value of the HX Series lies in its durability. The robust upper and lower frame structure that can endure external shock and high-load work and the attachments whose performance was proven by rigorous tests further show the real value of the HX Series in tough working environments and promise higher productivity.



Durable Cooling Module

The HX Series has a durable cooling module that passed stringent tests, demonstrating the highest productivity in tough working environments.



Reinforced Pin, Bush and Polymer Shim

The HX series improves lubricity of connecting parts between the equipment and attachments. Gaps with attachments are minimized by wear-resistant long-life pins, bushes and polymer shims, supporting the highest performance with invariable durability.



Reinforced Durability of Upper and Lower Structure and Attachments

The upper and lower structure and attachments of the HX Series have higher durability than demanded on the site, as proven through numerous tests including road tests and virtual simulation. The wear resistance of the bucket has been improved by use of new material.



*Photo may include optional equipment.

Hi-grade (High-pressure) Hoses

The HX Series uses high-pressure hoses with improved heat and pressure resistance, greatly increasing the durability of the equipment.



INFOTAINMENT FRONTIER

Enhanced Instrument Panel for Easier Monitoring

Many electronic functions are concentrated on the most convenient spot for operators to ensure work efficiency. The highly-advanced infotainment system, a product of HHI's intensive information technology, enables both productivity and pleasant work at the same time! The HX Series of HHI provides higher value and pleasure to customers.



Intelligent and Wide Cluster

The 8-inch capacitive-type display (like smartphone display) of the HX Series is 30% larger than the previous model, delivering excellent legibility. The centralized switches on the display allow convenience of checking the urea level and temperature outside the cabin. The audio AUX, air conditioner, heater interoperation and inclination sensor also maximize operator's convenience.

Wi-Fi Direct with Smart Phone (Miracast)

The Miracast system based on Wi-Fi of the operator's smart phone enables easy and convenient use of various features of the smart phone on the big screen including navigation, web surfing, viewing of videos, and listening to music. (For Android mobile phone now)



New Audio System

Radio player, USB-based MP3 player, integrated Bluetooth hands-free feature, and built-in microphone allow convenient phone calls while in work and in transit.

Proportional Auxiliary Hydraulic System

- Opt: Proportional control switch for better speed control
- Enlarge the operation convenience

MODERN COMFORT, SIMPLE AND SAFE SOLUTION

New Cabin for More Comfort

Low noise, low vibration, and ergonomic design make the cabin space more comfortable and pleasant! With focus on safety and convenience of operators, the HX Series allows rapid and safe equipment inspection anytime and anywhere, providing an optimal environment for operators to work.



Easy Access to DEF/AdBlue® Supply System

The DEF/AdBlue® tank is installed inside the tool box and its inlet is remotely located for easy access and convenient supply. Warning of overfill is given by a red lamp signal. The DEF/AdBlue® supply module is attached on the side of the fuel tank for easy maintenance and filter replacement.



Hi MATE (Remote Management System)

Hi MATE, Hyundai's proprietary remote management system, provides operators and dealer service personnel access to vital service and diagnostic information on the machine from any computer with internet access. Users can pinpoint machine location using digital mapping and set machine work boundaries, reducing the need for multiple service calls. Hi MATE saves time and money for the owner and dealer by promoting preventative maintenance and reducing machine downtime.

* Operation of the system may be affected by the condition of telecommunication signal



Swing Lock System (Option)

Swing Lock System is provided to maintain stability when swing movement needs to be limited, improving operating speed and productivity.

Fine Swing Control (Option)

Fine swing control is available for customer's convenience when users want to control fine swing.

SPECIFICATIONS

ENGINE					
Maker / Model		Perkins 1204F			
Type					
Water-cooled, 4-cycle diesel, 4-cylinder inline, Direct injection, Turbocharged, Charge and air cooled					
Rated flywheel horse power	SAE DIN	J1995 (gross) J1349 (net) 6271/1 (gross) 6271/1 (net)	92.7 kW (124 HP) at 1,950 rpm 87 kW (116 HP) at 1,950 rpm 92.7 kW (126 PS) at 1,950 rpm 87 kW (118 PS) at 1,950 rpm		
Max. torque			54.0 kgf-m (391 lbf-ft) at 1,400 rpm		
Bore x stroke			105 x 127 mm (4.1" x 5.0")		
Piston displacement			4,400 cc (268.5 cu in)		
Batteries			2 x 12 V x 100 Ah		
Starting motor			24 V - 4.5 kW		
Alternator			24 V - 100 A		
HYDRAULIC SYSTEM					
MAIN PUMP					
Type		Variable displacement tandem axis piston pumps			
Max. flow		2 x 126.8 l/min (33.5 US gpm / 27.9 UK gpm)			
Sub-pump for pilot circuit		Gear pump			
Cross-sensing and fuel saving pump system					
HYDRAULIC MOTORS					
Travel		Two speed axial pistons motor with brake valve and parking brake			
Swing		Axial piston motor with automatic brake			
RELIEF VALVE SETTING					
Implement circuits		350 kgf/cm² (4,980 psi)			
Travel		350 kgf/cm² (4,980 psi)			
Power boost (boom, arm, bucket)		380 kgf/cm² (5,410 psi)			
Swing circuit		285 kgf/cm² (4,050 psi)			
Pilot circuit		40 kgf/cm² (570 psi)			
Service valve		Installed			
HYDRAULIC CYLINDERS					
No. of cylinder bore x stroke		Boom: 2-105 x 1,105 mm (4.1" X 43.5") Arm: 1-115 x 1,138 mm (4.5" X 44.8") Bucket: 1-100 x 850 mm (3.9" X 33.1") Dozer Blade: 2-100 x 250 mm (3.9" X 9.8") 2-Piece Boom: 1st: 2-105 x 995 mm (4.1" x 39.2") 2nd: 1-145 x 613 mm (5.7" x 24.1")			
DRIVES & BRAKES					
Drive method		Fully hydrostatic type			
Drive motor		Axial piston motor, in-shoe design			
Reduction system		Planetary reduction gear			
Max. drawbar pull		12,000 kgf (26,455 lbf)			
Max. travel speed (high / low)		5.5 km/hr (3.4 mph) / 3.3 km/hr (2.1 mph)			
Gradeability		35° (70%)			
Parking brake		Multi wet disc			

CONTROL	
Pilot pressure operated joysticks and pedals with detachable lever provide almost effortless and fatigueless operation.	
Pilot control	Two joysticks with one safety lever (LH): Swing and arm (RH): Boom and bucket (ISO)
Traveling and steering	Two levers with pedals
Engine throttle	Electric, Dial type

SWING SYSTEM	
Swing motor	Fixed displacement axial piston motor
Swing reduction	Planetary gear reduction
Swing bearing lubrication	Grease-bathed
Swing brake	Multi wet disc
Swing speed	11.2 rpm

SERVICE REFILL CAPACITIES			
(): option			
Re-filling	liter	US gal	UK gal
Fuel tank	265	70.0	58.3
Engine coolant	14.5	3.8	3.2
Engine oil	10.5	2.8	2.3
Swing device	3.5 (2.5)	0.9 (0.7)	0.7 (0.5)
Final drive (each)	2.3	0.6	0.5
Hydraulic system (including tank)	180	47.6	39.6
Hydraulic tank	96	25.4	21.1
DEF/AdBlue® tank	19	5.0	4.2

UNDERCARRIAGE	
Center frame	X - leg type
Track frame	Pentagonal box type
No. of shoes on each side	47 EA
No. of carrier roller on each side	2 EA
No. of track roller on each side	7 EA
No. of rail guard on each side	1 EA

OPERATING WEIGHT (APPROXIMATE)				
Operating weight, including 4,600 mm (15' 1") boom; 2,500 mm (8' 2") arm; SAE heaped 0.52 m³ (0.68 yd³) bucket, lubricant, coolant, full fuel tank, full hydraulic tank and all standard equipments.				
Shoes	Operating weight	Ground pressure		
Type	Width mm (in)	kg (lb)	kgf/cm² (psi)	
	500 (20")	HX145LCR HX145LCR (Dozer type)	14,950 (32,960) 15,750 (34,720)	0.45 (6.40) 0.47 (6.68)
	600 (24")	HX145LCR HX145LCR (Dozer type)	15,160 (33,420) 15,960 (35,190)	0.38 (5.40) 0.40 (5.69)
	700 (28")	HX145LCR HX145LCR (Dozer type)	15,370 (33,880) 16,170 (35,650)	0.33 (4.69) 0.35 (4.98)

BUCKET SELECTION GUIDE & DIGGING FORCE

BUCKETS

All buckets are welded with high-strength steel.

SAE heaped m³ (yd³)	0.23 (0.30)	0.40 (0.52)	0.52 (0.68)	0.65 (0.85)	0.71 (0.93)	0.45 (0.59)	★ 0.55 (0.72)
---------------------	-------------	-------------	-------------	-------------	-------------	-------------	---------------

Capacity m³ (yd³)	Width mm (in)	Weight kg (lb)	Recommendation mm (ft.in)			
			4,600 (15' 1") Mono-boom		4,900 (16' 1") 2-Piece boom	
			1,900 (6' 3") Arm	2,100 (6' 11") Arm	2,500 (8' 2") Arm	3,000 (9' 10") Arm
0.23 (0.30)	0.20 (0.26)	520 (20.5)	620 (24.4)	335 (740)	●	●
0.40 (0.52)	0.35 (0.46)	750 (29.5)	850 (33.5)	410 (900)	●	●
0.46 (0.60)	0.40 (0.52)	840 (33.1)	940 (37.0)	435 (960)	●	●
0.52 (0.68)	0.45 (0.59)	915 (36.0)	1,015 (40.0)	460 (1,010)	●	●
0.58 (0.76)	0.50 (0.65)	1,000 (39.4)	1,100 (43.3)	480 (1,060)	●	●
0.65 (0.85)	0.55 (0.72)	1,105 (43.5)	1,205 (47.4)	500 (1,100)	■	▲
0.71 (0.93)	0.60 (0.78)	1,190 (46.9)	1,290 (50.8)	540 (1,190)	▲	-
0.45 (0.59)	0.40 (0.52)	1,520 (59.8)	-	410 (900)	●	■
0.55 (0.72)	0.45 (0.59)	1,800 (70.9)	-	585 (1,290)	■	▲

■ Ditching bucket

○ Slope finishing bucket

● : Applicable for materials with density of 2,000 kg /m³ (3,370 lb / yd³) or less

■ : Applicable for materials with density of 1,600 kg /m³ (2,700 lb / yd³) or less

▲ : Applicable for materials with density of 1,100 kg /m³ (1,850 lb / yd³) or less

ATTACHMENT

Booms and arms are welded with a low-stress, full-box section design.
4.6 m (15' 1") Mono-boom and 4.9 m (16' 1") 2-Piece boom and 1.9 m (6' 3"); 2.1 m (6' 11"); 2.5 m (8' 2") & 3.0 m (9' 10") Arms are available.

DIGGING FORCE


Arm	Bucket digging force	Length mm (ft.in)	1,900 (6' 3")	2,100 (6' 11")	2,500 (8' 2")	3,000 (9' 10")	Remarks:
Weight kg (lb)	560 (1,230)	580 (1,280)	610 (1,340)	670 (1,480)			
kN	87.3 [94.8]	87.3 [94.8]	87.3 [94.8]	87.3 [94.8]			

<tbl_r cells="8" ix="

DIMENSIONS & WORKING RANGE


HX145LCR DIMENSIONS

4.6 m (15' 1") Mono-boom and 2.1 m (6' 11"), 2.5 m (8' 2") & 3.0 m (9' 10") Arm.



A Tumbler distance	3,090 (10' 2")
B Overall length of crawler	3,798 (12' 4")
C Ground clearance of counterweight	930 (3' 1")
D Tail swing radius	1,500 (4' 11")
D' Rear-end length	1,500 (4' 11")
E Overall width of upperstructure	2,500 (8' 2")
F Overall height of cab	2,900 (9' 6")
G Min. ground clearance	440 (1' 5")
H Track gauge	2,000 (6' 7")
I Overall height of guardrail	3,215 (10' 7")
J Overall length	7,380 (24' 3")
K Overall height of boom	2,630 (8' 8")
L Track shoe width	500 (20")
M Overall width	2,500 (8' 2")
Boom length	4,600 (15' 1")
Arm length	1,900 (6' 3") 2,100 (6' 11") 2,500 (8' 2") 3,000 (9' 10")
O Height of blade	575 (1' 8")
P Overall height of guardrail	3,215 (10' 7")

HX145LCR WORKING RANGE




	Unit : mm (ft-in)
A Max. digging reach	7,730 (25' 4") 7,900 (25' 11") 8,310 (27' 3") 8,770 (28' 9")
A' Max. digging reach on ground	7,580 (24' 10") 7,750 (25' 0") 8,170 (26' 10") 8,630 (28' 4")
B Max. digging depth	4,890 (16' 1") 5,100 (16' 9") 5,500 (18' 1") 5,990 (19' 8")
B' Max. digging depth (8' level)	4,640 (15' 3") 4,870 (16' 0") 5,290 (17' 4") 5,810 (19' 1")
C Max. vertical wall digging depth	4,400 (14' 5") 4,600 (15' 1") 5,000 (16' 5") 5,400 (17' 9")
D Max. digging height	8,840 (29' 0") 8,970 (29' 5") 9,350 (30' 8") 9,730 (31' 11")
E Max. dumping height	6,350 (20' 10") 6,470 (21' 3") 6,850 (22' 6") 7,230 (23' 9")
F Min. front swing radius	1,860 (6' 1") 2,030 (6' 8") 1,980 (6' 6") 2,260 (7' 5")
Boom length	4,600 (15' 1")
Arm length	1,900 (6' 3") 2,100 (6' 11") 2,500 (8' 2") 3,000 (9' 10")

DIMENSIONS & WORKING RANGE


HX145LCR (DOZER TYPE) DIMENSIONS

4.6 m (15' 1") Mono-boom and 1.9 m (6' 3"), 2.1 m (6' 11"), 2.5 m (8' 2") & 3.0 m (9' 10") Arm.



A Tumbler distance	3,090 (10' 2")
B Overall length of crawler	3,798 (12' 4")
C Ground clearance of counterweight	930 (3' 1")
D Tail swing radius	1,500 (4' 11")
D' Rear-end length	1,500 (4' 11")
E Overall width of upperstructure	2,500 (8' 2")
F Overall height of cab	2,900 (9' 6")
G Min. ground clearance	440 (1' 5")
H Track gauge	2,000 (6' 7")
I Ground clearance of blade up	420 (1' 4")
J Overall length	7,840 (25' 9")
K Overall height of boom	2,630 (8' 8")
L Track shoe width	500 (20")
M Overall width	2,500 (8' 2")
Boom length	4,600 (15' 1")
Arm length	1,900 (6' 3") 2,100 (6' 11") 2,500 (8' 2") 3,000 (9' 10")
O Height of blade	575 (1' 8")
P Overall height of guardrail	3,215 (10' 7")

HX145LCR (DOZER TYPE) WORKING RANGE




	Unit : mm (ft-in)
A Max. digging reach	7,730 (25' 4") 7,900 (25' 11") 8,310 (27' 3") 8,770 (28' 9")
A' Max. digging reach on ground	7,580 (24' 10") 7,750 (25' 0") 8,170 (26' 10") 8,630 (28' 4")
B Max. digging depth	4,890 (16' 1") 5,100 (16' 9") 5,500 (18' 1") 5,990 (19' 8")
B' Max. digging depth (8' level)	4,640 (15' 3") 4,870 (16' 0") 5,290 (17' 4") 5,810 (19' 1")
C Max. vertical wall digging depth	4,400 (14' 5") 4,600 (15' 1") 5,000 (16' 5") 5,400 (17' 9")
D Max. digging height	8,840 (29' 0") 8,970 (29' 5") 9,350 (30' 8") 9,730 (31' 11")
E Max. dumping height	6,350 (20' 10") 6,470 (21' 3") 6,850 (22' 6") 7,230 (23' 9")
F Min. front swing radius	1,860 (6' 1") 2,030 (6' 8") 1,980 (6' 6") 2,260 (7' 5")
Boom length	4,600 (15' 1")
Arm length	1,900 (6' 3") 2,100 (6' 11") 2,500 (8' 2") 3,000 (9' 10")

DIMENSIONS & WORKING RANGE

HX145LCR 2-PIECE DIMENSIONS


4.9 m (16' 1") 2-piece boom and 2.1 m (6' 11"), 2.5 m (8' 2"), 3.05 m (10' 0") & 3.6 m (11' 10") Arm.



A	Tumbler distance	3,090 (10' 2")
B	Overall length of crawler	3,798 (12' 4")
C	Ground clearance of counterweight	930 (3' 1")
D	Tail swing radius	1,500 (4' 11")
D'	Rear-end length	1,500 (4' 11")
E	Overall width of upperstructure	2,500 (8' 2")
F	Overall height of cab	2,900 (9' 6")
G	Min. ground clearance	440 (1' 5")
H	Track gauge	2,000 (6' 7")
I	Overall height of guardrail	3,215 (10' 7")

Boom length	4,900 (16' 1") 2-Piece	
Arm length	2,100 (6' 11")	2,500 (8' 2")
J	Overall length	7,720 (25' 4")
K	Overall height of boom	2,870 (9' 5")
L	Track shoe width	500 (20") 600 (24") 700 (28")
M	Overall width	2,500 (8' 2") 2,600 (8' 6") 2,700 (8' 10")


HX145LCR 2-PIECE WORKING RANGE



DIMENSIONS & WORKING RANGE

HX145LCR 2-PIECE (DOZER TYPE) DIMENSIONS


4.9 m (16' 1") 2-piece boom and 2.1 m (6' 11") & 2.5 m (8' 2") Arm.



A	Tumbler distance	3,090 (10' 2")
B	Overall length of crawler	3,798 (12' 4")
C	Ground clearance of counterweight	930 (3' 1")
D	Tail swing radius	1,500 (4' 11")
D'	Rear-end length	1,500 (4' 11")
E	Overall width of upperstructure	2,500 (8' 2")
F	Overall height of cab	2,900 (9' 6")
G	Min. ground clearance	440 (1' 5")
H	Track gauge	2,000 (6' 7")
I	Ground clearance of blade up	410 (1' 4")
N	Depth of blade down	450 (1' 5")
O	Height of blade	575 (1' 8")
P	Overall height of guardrail	3,215 (10' 7")

Boom length	4,900 (16' 1") 2-Piece	
Arm length	2,100 (6' 11")	2,500 (8' 2")
J	Overall length	8,180 (26' 10") 8,150 (26' 9")
K	Overall height of boom	2,870 (9' 5") 2,900 (9' 6")
L	Track shoe width	500 (20") 600 (24") 700 (28")
M	Overall width	2,500 (8' 2") 2,600 (8' 6") 2,700 (8' 10")

HX145LCR 2-PIECE (DOZER TYPE) WORKING RANGE



LIFTING CAPACITY

		Rating over-front		Rating over-side or 360 degrees	

HX145LCR

Boom: 4.6 m (15' 1") / Arm: 1.9 m (6' 3") / Bucket: 0.52 m³ (0.68 yd³) SAE heaped / Shoe: 600 mm (24") triple grouser with 2,800 kg (6,170 lb) counterweight.

Load point height m (ft)	Load radius				At max. reach	
	1.5 m (5 ft)	3.0 m (10 ft)	4.5 m (15 ft)	6.0 m (20 ft)	Capacity	Reach
6.0 m (20 ft) kg			*3240 *7140	*3240 *7140	*3720 *8200	2200 4850 (18.9)
4.5 m (15 ft) kg			*5040 *11110	*5040 *11110	*4330 *9550	2830 6240 (22.1)
3.0 m (10 ft) kg			*7250 *15980	6120 13490	*5010 *11050	3140 6920 (23.7)
1.5 m (5 ft) kg			*9050 *19950	5370 11840	5240 11550	2890 6370 (24.0)
Ground Line kg			*8630 *19030	5110 11270	5050 6000	2720 7010 (23.2)
-1.5 m (-5 ft) kg	*6890 *15190	*6890 *15190	*8100 *17860	5120 11290	4990 11000	2670 5890 (21.0)
-3.0 m (-10 ft) kg			*5970 *13160	5250 11570	*4070 *8970	2740 6040 (16.8)

Boom: 4.6 m (15' 1") / Arm: 2.1 m (6' 11") / Bucket: 0.52 m³ (0.68 yd³) SAE heaped / Shoe: 600 mm (24") triple grouser with 2,800 kg (6,170 lb) counterweight.

Load point height m (ft)	Load radius				At max. reach	
	1.5 m (5 ft)	3.0 m (10 ft)	4.5 m (15 ft)	6.0 m (20 ft)	Capacity	Reach
6.0 m (20 ft) kg			*3440 *7580	3420 7540		3550 7830 (19.6)
4.5 m (15 ft) kg			*4410 *9720	*4410 *9720	*2550 *5620	1970 4340 (22.7)
3.0 m (10 ft) kg			*6880 *15170	6200 13670	*4840 *10670	3150 6940 (24.2)
1.5 m (5 ft) kg			*9010 *19860	5410 11930	5250 6370	2890 3990 (24.6)
Ground Line kg			*8880 *19580	5090 11220	5030 1090	2700 5950 (23.8)
-1.5 m (-5 ft) kg	*6570 *14480	*6570 *14480	*8330 *18360	5060 11160	4950 10910	2630 5800 (21.7)
-3.0 m (-10 ft) kg			*9010 *19860	5100 11400	*6340 *13980	4340 9570 (17.7)

Boom: 4.6 m (15' 1") / Arm: 2.5 m (8' 2") / Bucket: 0.52 m³ (0.68 yd³) SAE heaped / Shoe: 600 mm (24") triple grouser with 2,800 kg (6,170 lb) counterweight.

Load point height m (ft)	Load radius				At max. reach		
	1.5 m (5 ft)	3.0 m (10 ft)	4.5 m (15 ft)	6.0 m (20 ft)	Capacity	Reach	
6.0 m (20 ft) kg			*2960 *6530	*2960 *6530		*2920 *6440	1750 3860 (21.3)
4.5 m (15 ft) kg			*3480 *7670	3400 7500	*2670 *5890	1990 4390 (24.2)	
3.0 m (10 ft) kg			*6110 *13470	*6110 *13470	*4490 *9900	3180 7010 (25.6)	
1.5 m (5 ft) kg			*8480 *18700	5520 12170	5260 11600	2890 6370 (25.9)	
Ground Line kg			*9170 *20220	5070 11180	5010 11050	2670 5890 (25.2)	
-1.5 m (-5 ft) kg	*5880 *12960	*5880 *12960	*8680 *19140	4960 10930	4890 10780	2570 5670 (23.2)	
-3.0 m (-10 ft) kg			*8960 *19750	8960 19750	*7000 *15430	5040 11110	
-4.5 m (-15 ft) kg			*3710 *8180	*3710 *8180	*4750 *10470	2590 5710	

1. Lifting capacity are based on SAE J1097 and ISO 10567.

2. Lifting capacity of the HX series does not exceed 75% of tipping load with the machine on firm, level ground or 87% of full hydraulic capacity.

3. The load point is a hook (standard equipment) located on the back of the bucket.

4. (*) indicates load limited by hydraulic capacity.

LIFTING CAPACITY

		Rating over-front		Rating over-side or 360 degrees	

HX145LCR

Boom: 4.6 m (15' 1") / Arm: 3.0 m (9' 10") / Bucket: 0.52 m³ (0.68 yd³) SAE heaped / Shoe: 600 mm (24") triple grouser with 2,800 kg (6,170 lb) counterweight.

Load point height m (ft)	Load radius				At max. reach	
	1.5 m (5 ft)	3.0 m (10 ft)	4.5 m (15 ft)	6.0 m (20 ft)	Capacity	Reach
6.0 m (20 ft) kg					*2580 *5690	*1710 *3770
4.5 m (15 ft) kg					*2790 *6150	*2570 *6150
3.0 m (10 ft) kg					*3770 *8310	*3240 *8250
1.5 m (5 ft) kg					*7770 *17130	*1820 *12720
Ground Line kg					*9190 *20260	*1230 *2710
-1.5 m (-5 ft) kg	*5400 *11900	*5400 *11900			*9050 *19950	*4970 *10960
-3.0 m (-10 ft) kg					*7890 *17390	*4870 *11000
-4.5 m (-15 ft) kg					*5120 *11290	*3220 *7100

Boom: 4.6 m (15' 1") / Arm: 1.9 m (6' 3") / Bucket: 0.52 m³ (0.68 yd³) SAE heaped / Shoe: 600 mm (24") triple grouser with 2,800 kg (6,170 lb) counterweight. Dozer Blade up

Load point height m (ft)	Load radius				At max. reach	
	1.5 m (5 ft)	3.0 m (10 ft)	4.5 m (15 ft)	6.0 m (20 ft)	Capacity	Reach
6.0 m (20 ft) kg					*3240 *7140	*3240 *7140
4.5 m (15 ft) kg					*5040 *11110	*5350 *7780
3.0 m (10 ft) kg					*7250 *15980	*3330 *14220
1.5 m (5 ft) kg					*9050 *19950	*3080 *12020
Ground Line kg					*8630 *19030	*2910 *11600
-1.5 m (-5 ft) kg	*6890 *15190	*6890 *15190			*8100 *17860	*2860 *12020
-3.0 m (-10 ft) kg					*5970 *13160	*2930 *8970

Boom: 4.6 m (15' 1") / Arm: 1.9 m (6' 3") / Bucket: 0.52 m³ (0.68 yd³) SAE heaped / Shoe: 600 mm (24") triple grouser with 2,800 kg (6,170 lb) counterweight. Dozer Blade down

Load point height m (ft)	Load radius				At max. reach	
1.5 m (5 ft)	3.0 m (10 ft)	4.5 m (15 ft)	6.0 m (20 ft)	Capacity	Reach	

<tbl_r

LIFTING CAPACITY

		Rating over-front		Rating over-side or 360 degrees					
HX145LCR									
Boom: 4.6 m (15' 1") / Arm: 2.1 m (6' 11") / Bucket: 0.52 m ³ (0.68 yd ³) SAE heaped / Shoe: 600 mm (24") triple grouser with 2,800 kg (6,170 lb) counterweight. Dozer Blade up									

Load point height m (ft)	kg (lb)	Load radius				At max. reach					
		1.5 m (5 ft)	3.0 m (10 ft)	4.5 m (15 ft)	6.0 m (20 ft)	Capacity	Reach				
6.0 m (20 ft)	kg (lb)			*3440 *7580	*3440 *7580		*3550 *7830	2200 4850	5.98 (19.6)		
4.5 m (15 ft)	kg (lb)	*4410 *9720	*4410 *9720	*4150 *9150	3550 7830	*2550 *5620	2110 4650	2810 6190	1640 3620	6.92 (22.7)	
3.0 m (10 ft)	kg (lb)	*6880 *15170	6530 14400	*4840 *10670	3340 7360	3510 4500	2040 5420	2460 3090	1400 3090	7.39 (24.2)	
1.5 m (5 ft)	kg (lb)	*9010 *19860	5750 12680	5450 12020	3080 6790	3400 7500	1940 4280	2360 5200	1320 2910	7.49 (24.6)	
Ground Line	kg lb	*8880 *19580	5420 11950	5240 11550	2890 6370	3300 7280	1850 4080	2460 5420	1370 3020	7.24 (23.8)	
-1.5 m (-5 ft)	kg (lb)	*6570 *14480	*6570 *14480	*8330 *18360	5390 11880	5160 6220	2820 7210	3270 4030	1830 6310	2860 3550	6.60 (21.7)
-3.0 m (-10 ft)	kg (lb)	*9010 *19860	*9010 *19860	*6340 *13980	5510 12150	*4340 *9570	2870 6330		*2390 *5270	2290 5050	5.38 (17.7)

Boom: 4.6 m (15' 1") / Arm: 2.1 m (6' 11") / Bucket: 0.52 m ³ (0.68 yd ³) SAE heaped / Shoe: 600 mm (24") triple grouser with 2,800 kg (6,170 lb) counterweight. Dozer Blade down												
Load point height m (ft)	kg (lb)	Load radius				At max. reach						
1.5 m (5 ft)	3.0 m (10 ft)	4.5 m (15 ft)	6.0 m (20 ft)	Capacity	Reach	m (ft)						
6.0 m (20 ft)	kg (lb)			*3440 *7580	*3440 *7580		*3550 *7830	2460 5420	5.98 (19.6)			
4.5 m (15 ft)	kg (lb)	*4410 *9720	*4410 *9720	*4150 *9150	3960 8730	*2550 *5620	2360 5200	*3420 *7540	1840 4060	6.92 (22.7)		
3.0 m (10 ft)	kg (lb)	*6880 *15170	6880 15170	*4840 *10670	3740 8250	*3960 *8730	2300 5070	*3370 *7430	1590 3510	7.39 (24.2)		
1.5 m (5 ft)	kg (lb)	*9010 *19860	6600 14550	*5630 *12410	3470 7650	*4230 *9330	2190 4830	*3330 *7340	1500 3310	7.49 (24.6)		
Ground Line	kg lb	*8880 *19580	6260 13800	*5990 *13210	3280 7230	*4320 *9520	2100 4630	*3260 *7190	1570 3460	7.24 (23.8)		
-1.5 m (-5 ft)	kg (lb)	*6570 *14480	*6570 *14480	*8330 *18360	6230 13730	*5650 *12460	3210 7080	*3890 *8580	2080 4590	*3050 *6720	1830 4030	6.60 (21.7)
-3.0 m (-10 ft)	kg (lb)	*9010 *19860	*9010 *19860	*6340 *13980	*6340 *13980	*4340 *9570	3260 7190		*2390 *5270	*2390 *5270	5.38 (17.7)	

Boom: 4.6 m (15' 1") / Arm: 2.5 m (8' 2") / Bucket: 0.52 m ³ (0.68 yd ³) SAE heaped / Shoe: 600 mm (24") triple grouser with 2,800 kg (6,170 lb) counterweight. Dozer Blade up										
Load point height m (ft)	kg (lb)	Load radius				At max. reach				
1.5 m (5 ft)	3.0 m (10 ft)	4.5 m (15 ft)	6.0 m (20 ft)	Capacity	Reach	m (ft)				
6.0 m (20 ft)	kg (lb)			*2970 *6550	*2970 *6550		*2920 *6440	1880 4140	6.50 (21.3)	
4.5 m (15 ft)	kg (lb)			*3490 *7690	*3490 *7690		*2670 *5250	2380 5250	6.760 (24.2)	
3.0 m (10 ft)	kg (lb)	*6120 *13490	*6120 *13490	*4490 *9900	3370 7430	2040 4500	2220 4890	*3780 *2830	2300 5070	7.390 (25.6)
1.5 m (5 ft)	kg (lb)	*8490 *18720	5870 12940	*5370 *11840	3090 6810	3390 7470	1930 4250	*5370 *4250	3490 7690	7.490 (24.6)
Ground Line	kg lb	*9170 *20220	5410 11510	*5220 *6330	2870 7210	3270 4010	1820 4890	*1210 *2670	2120 4260	7.670 (25.2)
-1.5 m (-5 ft)	kg (lb)	*5870 *12940	*5870 *12940	*8690 *19160	5310 11710	5110 11270	2770 6110	*1710 *3110	1710 5970	7.07 (23.2)
-3.0 m (-10 ft)	kg (lb)	*8960 *19750	*8960 *19750	*7010 *15450	5390 11880	*4760 *10490	2790 6150	*4760 *10490	1890 4170	5.97 (19.6)
-4.5 m (-15 ft)	kg (lb)			*3710 *8180	*3710 *8180					

1. Lifting capacity are based on SAE J1097 and ISO 10567.
 2. Lifting capacity of the HX series does not exceed 75% of tipping load with the machine on firm, level ground or 87% of full hydraulic capacity.

3. The load point is a hook (standard equipment) located on the back of the bucket.
 4. (*) indicates load limited by hydraulic capacity.

LIFTING CAPACITY

		Rating over-front		Rating over-side or 360 degrees					
HX145LCR									
Boom: 4.6 m (15' 1") / Arm: 2.5 m (8' 2") / Bucket: 0.52 m ³ (0.68 yd ³) SAE heaped / Shoe: 600 mm (24") triple grouser with 2,800 kg (6,170 lb) counterweight. Dozer Blade down									

Load point height m (ft)	kg (lb)	Load radius				At max. reach			
		1.5 m (5 ft)	3.0 m (10 ft)	4.5 m (15 ft)	6.0 m (20 ft)	Capacity	Reach		
6.0 m (20 ft)	kg (lb)			*2970 *6550	*2970 *6550		*2920 *6440	2100 4630	6.50 (21.3)
4.5 m (15 ft)	kg (lb)			*3490 *7690	*3490 *7690		*2670 *5250	1630 3590	7.37 (24.2)
3.0 m (10 ft)	kg (lb)	*6120 *13490	6530 13490	*4490 *9900	3370 7430	3440 4500	*3780 *2830	2300 5070	7.81 (25.6)
1.5 m (5 ft									

LIFTING CAPACITY

LIFTING CAPACITY

 Rating over-front  Rating over-side or 360 degrees

HX145LCR 2-PIECE BOOM

Boom: 4.9 m (16' 1") / Arm: 2.1 m (6' 11") / Bucket: 0.52 m³ (0.68 yd³) SAE heaped / Shoe: 600 mm (24") triple grouser with 2,800 kg (6,170 lb) counterweight.

Load point height m (ft)	Load radius						At max. reach				
	1.5 m (5 ft)		3.0 m (10 ft)		4.5 m (15 ft)		6.0 m (20 ft)		Capacity	Reach	
									m (ft)		
6.0 m (20 ft) kg lb	*3480 *7670	*3480 *7670	*3700 *8160	*3700 *8160	*3490 *7690	3470 7650			3100 6830	1770 3900	6.46 (21.2)
4.5 m (15 ft) kg lb	*3410 *7520	*3410 *7520	*4460 *9830	*4460 *9830	*3800 *8380	3350 7390	*3410 *7520	1980 4370	2430 5360	1330 2930	7.33 (24.0)
3.0 m (10 ft) kg lb			*6790 *14970	5990 13210	*4560 *10050	3090 6810	3360 7410	1880 4140	2140 4720	1140 2510	7.77 (25.5)
1.5 m (5 ft) kg lb					5170 11400	2790 6150	3230 7120	1760 3880	2060 4540	1070 2360	7.87 (25.8)
Ground Line kg lb			*5960 *13140	4890 10780	4950 10910	2600 5730	3120 6880	1660 3660	2140 4720	1110 2450	7.63 (25.0)
-1.5 m (-5 ft) kg lb			*8260 *18210	4900 10800	4880 10760	2540 5600	3080 6790	1620 3570			

Boom: 4.9 m (16' 1") / Arm: 2.5 m (8' 2") / Bucket: 0.52 m³ (0.68 yd³) SAE heaped / Shoe: 600 mm (24") triple grouser with 2,800 kg (6,170 lb) counterweight.

Load point height m (ft)	Load radius						At max. reach				
	1.5 m (5 ft)		3.0 m (10 ft)		4.5 m (15 ft)		6.0 m (20 ft)		Capacity	Reach	
									m (ft)		
6.0 m (20 ft) kg lb	*2640 *5820	*2640 *5820	*3000 *6610	*3000 *6610	*3110 *6860	*3110 *4390	*1990 *4390	*1990 *4390	2700 5950	1510 3330	6.96 (22.8)
4.5 m (15 ft) kg lb	*2270 *5000	*2270 *5000	*3170 *6990	*3170 *6990	*3440 *7580	3390 7470	*3140 *6920	1990 4390	2170 4780	1160 2560	7.77 (25.5)
3.0 m (10 ft) kg lb			*6030 *13290	*6030 *13290	*4220 *9300	3120 6880	3370 7430	1880 4140	1930 4250	1000 2200	8.18 (26.8)
1.5 m (5 ft) kg lb			*7680 *16930	*5260 *11600	*5120 *11290	2800 6170	3210 7080	1740 3840	2190 4830	1140 2510	8.27 (27.1)
Ground Line kg lb			*6290 *13870	4850 10690	4930 10870	2570 5670	3090 6810	1620 3570	1920 4230	970 2140	8.05 (26.4)
-1.5 m (-5 ft) kg lb			*8510 *18760	4800 10580	4810 10600	2470 5450	3020 6660	1570 3460	2170 4780	1120 2470	7.49 (24.6)
-3.0 m (-10 ft) kg lb					4840 10670	2500 5510					

Boom: 4.9 m (16' 1") / Arm: 2.1 m (6' 11") / Bucket: 0.52 m³ (0.68 yd³) SAE heaped / Shoe: 600 mm (24") triple grouser with 2,800 kg (6,170 lb) counterweight. Dozer Blade up

Load point height m (ft)	Load radius						At max. reach				
	1.5 m (5 ft)		3.0 m (10 ft)		4.5 m (15 ft)		6.0 m (20 ft)		Capacity	Reach	
									m (ft)		
6.0 m (20 ft) kg lb	*3480 *7670	*3480 *7670	*3700 *8160	*3700 *8160	*3490 *7690				*3150 *6940	1890 4170	6.46 (21.2)
4.5 m (15 ft) kg lb	*3410 *7520	*3410 *7520	*4460 *9830	*4460 *9830	*3800 *8380	3540 7800	*3410 *7520	2110 4650	2540 5600	1440 1370	7.33 (24.0)
3.0 m (10 ft) kg lb			*6790 *14970	6330 13960	*4560 *10050	3280 7230	3500 7720	2010 4430	2240 4940	1240 2730	7.77 (25.5)
1.5 m (5 ft) kg lb					5380 11860	2980 6570	3370 7430	1890 4170	2160 4760	1170 2580	7.87 (25.8)
Ground Line kg lb			*5960 *13140	5230 11530	5160 11380	2790 6150	3260 7190	1790 3950	2240 4940	1210 2670	7.63 (25.0)
-1.5 m (-5 ft) kg lb			*8260 *18210	5240 11550	5080 11200	2720 6000	3220 7100	1760 3880			

1. Lifting capacity are based on SAE J1097 and ISO 10567.
2. Lifting capacity of the HX series does not exceed 75% of tipping load with the machine on firm, level ground or 87% of full hydraulic capacity.

3. The load point is a hook (standard equipment) located on the back of the bucket.
4. (*) indicates load limited by hydraulic capacity.

 Rating over-front  Rating over-side or 360 degrees

HX145LCR 2-PIECE BOOM

Boom: 4.9 m (16' 1") / Arm: 2.1 m (6' 11") / Bucket: 0.52 m³ (0.68 yd³) SAE heaped / Shoe: 600 mm (24") triple grouser with 2,800 kg (6,170 lb) counterweight. Dozer Blade down

Load point height m (ft)	Load radius						At max. reach		
1.5 m (5 ft)		3.0 m (10 ft)		4.5 m (15 ft)		6.0 m (20 ft)		Capacity	Reach
									m (ft)

<tbl_r cells="3" ix="1" maxcspan="6

NOTES

NOTES

ENGINE	STD	OPT	STD	OPT
Perkins 1204F engine	●			
HYDRAULIC SYSTEM				
Intelligent Power Control (IPC)				
3-power mode, 2-work mode, user mode	●			
Variable Power Control	●			
Pump Flow Control	●			
Attachment Mode Flow Control		●		
Engine Auto Idle	●			
Engine Auto Shutdown Control		●		
Electronic Fan Control	●			
CABIN & INTERIOR				
ISO Standard cabin				
Rise-up type windshield wiper	●			
Radio / USB player	●			
Handsfree mobile phone system with USB	●			
12 volt power outlet (24V DC to 12V DC converter)	●			
Electric horn	●			
All-weather steel cab with 360° visibility	●			
Safety glass windows	●			
Sliding fold-in front window	●			
Sliding side window (LH)	●			
Lockable door	●			
Hot & cool box	●			
Storage compartment & Ashtray	●			
Transparent cabin roof-cover	●			
Sun visor	●			
Door and cab locks, one key	●			
Mechanical suspension seat with heater	●			
Pilot-operated slideable joystick	●			
Console box height adjust system	●			
Automatic climate control				
Air conditioner & heater	●			
Defroster	●			
Starting Aid (air grid heater) for cold weather	●			
Centralized monitoring				
8" LCD display	●			
Engine speed or Trip meter/Accel.	●			
Engine coolant temperature gauge	●			
Max power	●			
Low speed/High speed	●			
Auto idle	●			
Overload	●			
Check Engine	●			
Air cleaner clogging	●			
Indicators	●			
ECO Gauges	●			
Fuel level gauge	●			
Hyd. oil temperature gauge	●			
Warnings	●			
Communication error	●			
Low battery	●			
Clock	●			
Cabin lights	●			
Cabin front window rain guard	●			
Seat				
Adjustable air suspension seat with heater		●		
Cabin FOPS/FOG (ISO/DIS 10262) Level 2				
FOPS (Falling Object Protective Structure) · ISO 3449 Level 2		●		
FOG (Falling Object Guard)		●		
Cabin ROPS (ISO 12117-2)				
ROPS (Roll Over Protective Structure)	●			
SAFETY				
Battery master switch		●		
Rearview camera		●		
Four front working lights		●		
Travel alarm		●		
Rear work lamp			●	
Beacon lamp			●	
Automatic swing brake		●		
Boom holding system		●		
Arm holding system		●		
Safety lock valve for boom cylinder with overload warning device		●		
Safety lock valve for arm cylinder			●	
Swing Lock System			●	
Two outside rearview mirrors		●		
OTHER				
Booms				
4.6 m; 15' 1" Mono		●		
4.1 m m; 13' 5" Mono			●	
4.9 m; 16' 1" 2-Piece			●	
Arms				
1.9 m; 6' 3"			●	
2.1 m; 6' 11"			●	
2.5 m; 8' 2"			●	
3.0 m; 9' 11"			●	
Removable clean-out dust net for cooler		●		
Removable reservoir tank		●		
Fuel pre-filter		●		
Self-diagnostics system		●		
Hi MATE (Remote Management System)		●		
Batteries (2 x 12 V x 100 Ah)		●		
Fuel filler pump (50 l/min)		●		
Single-acting piping kit (breaker, etc.)			●	
Double-acting piping kit (clamshell, etc.)			●	
Rotating Piping Kit			●	
Quick coupler piping			●	
Quick coupler			●	
Accumulator for lowering work equipment		●		
Pattern change valve (2 patterns)			●	
Fine Swing Control System			●	
Tool kit			●	
UNDERCARRIAGE				
Lower frame under cover (Additional)			●	
Lower frame under cover (Normal)		●		
Track shoes				
Triple grouser shoe (600 mm; 24")		●		
Triple grouser shoe (700 mm; 28")			●	
Track rail guard			●	

STD = Standard

OPT = Optional

* Standard and optional equipment may vary. Contact your Hyundai dealer for more information.
The machine may vary according to International standards.

* The photos may include attachments and optional equipment that are not available in your area.

* Materials and specifications are subject to change without advance notice.

* All imperial measurements rounded off to the nearest pound or inch.

* The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant HFC-134a (Global Warming Potential = 1430). The system contains 0.75 kg of refrigerant which has a CO₂ equivalent of 1.0725 metric tonne.



PLEASE CONTACT